

(19)

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 965 975 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
22.12.1999 Bulletin 1999/51

(51) Int Cl.<sup>6</sup>: **G09G 3/28**(21) Application number: **99304808.1**(22) Date of filing: **18.06.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **18.06.1998 JP 17082598**  
**09.03.1999 JP 6166099**

(71) Applicant: **FUJITSU LIMITED**  
**Kawasaki-shi, Kanagawa 211-8588 (JP)**


(72) Inventors:  
• **Setoguchi, Noriaki,**  
**KYUSHU FUJITSU ELECTRONICS LTD**  
**Satsuma-gun, Kagoshima 895-1493 (JP)**  
• **Asao, Shigeharu, c/o FUJITSU LIMITED**  
**Kawasaki-shi, Kanagawa 211-8588 (JP)**  
• **Kanazawa, Yoshikazu, c/o FUJITSU LIMITED**  
**Kawasaki-shi, Kanagawa 211-8588 (JP)**

(74) Representative: **Fenlon, Christine Lesley et al**  
**Haseltine Lake & Co.,**  
**Imperial House,**  
**15-19 Kingsway**  
**London WC2B 6UD (GB)**

**(54) Method and apparatus for driving plasma display panel**

(57) A plasma display panel may have a plurality of first electrodes and second electrodes are arranged parallel to each other, a plurality of third electrodes are arranged to cross the first and second electrodes, and discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix. According to a driving method for such a plasma display panel, a reset period is a period during which the distribution of wall charges in the plurality of discharge cells is uniformed. An addressing period is a period during which wall charges are produced in the discharge cells

according to display data. A sustain discharge period is a period during which sustain discharge is induced in the discharge cells in which wall charges are produced during the addressing period. The driving method comprises a step of applying a first pulse ( $-V_{wx}$ ,  $V_{wy}$ ) in which an applied voltage varies with time so as to induce first discharge in the lines defined by the first and second electrodes, and a step of applying a second pulse ( $V_{ex}$ ,  $-V_{ey}$ ) in which an applied voltage varies with time so as to induce second discharge as erase discharge in the lines defined by the first and second electrodes. These steps are carried out during the reset period.

**EP 0 965 975 A1**

## Description

[0001] The present invention relates to a method and apparatus for driving a plasma display panel (PDP).

[0002] The PDP is a self-luminous type display device with a characteristic good discernment (i.e., high resolution) and with a thin and large display screen. The PDP is attracting attention as a display device with which CRTs will be replaced in the near future. In particular, a surface discharge AC type PDP is highly expected to be a display device compatible with high-quality digital broadcasting, because it can be designed to have a large display screen. The surface discharge AC type PDP will be required to provide a higher quality than a CRT.

[0003] A high-quality display may be construed as a high-definition display, a display with a large number of gray-scale levels, a high-luminance display, or a high-contrast display. A high-definition display is accomplished by setting the pitch between pixels to a small value. A display with a large number of gray-scale levels is accomplished by increasing the number of sub-fields within a frame. Moreover, a high-luminance display is accomplished by increasing the amount of visible light permitted by certain power or increasing the number of times of sustain discharge. Furthermore, a high-contrast display is accomplished by minimizing the reflectance of extraneous light from the surface of a display panel or minimizing an amount of glow that occurs during black display which does not contribute to the display.

[0004] The structure of a previously-considered plasma display panel and a previously-considered method for driving a plasma display panel will be described with reference to Fig. 1 to Fig. 4 of the accompanying drawings. This is intended to facilitate an understanding of problems underlying the previously-considered method for driving a plasma display panel.

[0005] Fig. 1 schematically shows the structure of a surface discharge type PDP, as disclosed in, for example, the specification and drawings of Japanese Unexamined Patent Publication No. 9-160525 published on June 20, 1997. In such a PDP, a method in which lines defined by all sustain discharge electrodes are involved in display, can be implemented.

[0006] A PDP 1 consists of sustain discharge electrodes X1 to X3 (hereinafter abbreviated to X1 to X3 electrodes) and Y1 to Y3 (hereinafter abbreviated to Y1 to Y3 electrodes), addressing electrodes A1 to A4, and barriers 2. The above sustain discharge electrodes are juxtaposed in parallel with each other on one substrate. The addressing electrodes are formed to cross the sustain discharge electrodes on the other substrate. The barriers 2 are arranged in parallel with the addressing electrodes, thus separating discharge spaces from each other. A discharge cell is formed in areas defined by the mutually adjoining sustain discharge electrodes and the addressing electrodes crossing the sustain discharge electrodes. Phosphors used to produce visible light are

placed in the discharge cells. A gas for bringing about discharge is sealed in a space between the substrates. In this drawing, for brevity's sake, the sustain discharge electrodes are arranged parallel to each other in threes, and the addressing electrodes number four.

[0007] In the PDP having the foregoing structure, sustain discharge is induced in lines defined by each sustain discharge electrode and sustain discharge electrodes on both sides thereof. Interspaces or lines (L1 to L5) defined by all the electrodes therefore can work as display lines. For example, the X1 electrode and Y1 electrode define a display line L1, and the Y1 electrode and X2 electrode define a display line L2.

[0008] Fig. 2 shows a sectional view of the PDP shown in Fig. 1 along an addressing electrode. There are shown a front substrate 3, a back substrate 4, and discharges D1 to D3 induced in lines defined by electrodes. In practice, a voltage is applied to the Y1 electrode and X1 electrode. This induces the discharge D1. When a voltage is applied to the Y1 electrode and X2 electrode, the discharge D2 is induced. The discharge D3 is induced by applying a voltage to the X2 electrode and Y2 electrode. Thus, one electrode is utilized for providing display lines on both sides thereof. Consequently, a high-definition display can be achieved owing to a decreased number of electrodes. Besides, the number of drive circuits for driving the electrodes can be reduced accordingly.

[0009] Fig. 3 shows a frame configuration employed in the PDP shown in Fig. 1. One frame is composed of two fields of a first field and second field. During the first field, odd-numbered lines (L1, L3 and L5) are used as display lines to be involved in the display. During the second field, even-numbered lines (L2, L4) are used as display lines to be involved in the display. Thus, a picture for one screen is displayed during one frame. Each field consists of a plurality of sub-fields for which luminance levels are set in a predetermined ratio. Cells constituting display lines are selectively allowed to glow according to display data during the sub-fields. Thus, gray-scale levels construed as differences in luminance among pixels are expressed. Each sub-field consists of a reset period, an addressing period, and a sustain discharge period. During the reset period, the states of cells that are mutually different depending on the display situation over an immediately preceding sub-field are uniformed. During the addressing period, new display data is written. During the sustain discharge period, sustain discharge is induced in the cells constituting display lines so that the cells are allowed to glow according to display data.

[0010] Fig. 4 is a waveform diagram for use in explaining a driving method which can be implemented in the PDP shown in Fig. 1. Fig. 4 is concerned with any sub-field within the first field.

[0011] During the reset period, a reset pulse of a voltage  $V_w$  exceeding a discharge start voltage is applied to all the X electrodes. Discharge is initiated in the lines

defined by the X electrodes and adjoining Y electrodes. As a result, first discharge (reset discharge) is induced in all the lines (L1 to L5). Wall charges including positively-charged ions and electrons are produced in the discharge cells. Thereafter, the reset pulse is removed and the electrodes are retained at the same potential. Second discharge (self-erase discharge) is then induced due to the potential difference generated by the wall charges produced on the electrodes. At this time, since the electrodes are retained at the same potential, positively-charged ions and electrons stemming from discharge are recombined with each other within the discharge spaces. Consequently, the wall charges disappear. The magnitude of wall charges in all the display cells can be uniformed with the discharge (the distribution of wall charges is uniformed).

[0012] During the next addressing period, a scanning pulse of a voltage  $-V_y$  is applied successively to the electrodes starting with the Y1 electrode. An addressing pulse of a voltage  $V_a$  is applied to the addressing electrodes according to display data. Consequently, addressing discharge is initiated. At this time, a pulse of a voltage  $V_x$  is applied to the X1 electrode to be paired with the Y1 electrode to participate in the display within the first field. Discharge having been induced in the spaces defined by the addressing electrodes and the Y1 electrode shifts to the line between the X1 electrode and Y1 electrode. Consequently, wall charges needed to initiate sustain discharge are produced near the X1 electrode and Y1 electrode. The potential at the X2 electrode to be paired with the Y1 electrode to define a line not involved in the display is retained at 0 V. It is therefore prevented that discharge is induced in the line defined by the X2 electrode. Likewise, addressing discharge is induced successively in the odd-numbered Y electrodes.

[0013] After the addressing discharge induced in the odd-numbered Y electrodes is completed, a scanning pulse is applied to the Y2 electrode. At this time, a pulse of a voltage  $V_x$  is applied to the X2 electrode to be paired with the Y2 electrode to thus participate in the display. The X3 electrode that is not shown is, like the X1 electrode, retained at 0 V. Likewise, addressing discharge is induced successively in the even-numbered Y electrodes. Consequently, addressing discharge is induced in the odd lines in the whole screen.

[0014] Thereafter, during the sustain discharge period, sustain pulse of a voltage  $V_s$  is applied alternately to the X electrodes and Y electrodes. At this time, the phase of the sustain pulse is set so that a potential difference between paired electrodes defining a line not involved in display will be 0 V. It is thus prevented that discharge is induced in non-display lines. For example, sustain pulses that are mutually out of phase are applied to the pair of the X1 and Y1 electrodes participating in the display over the first field. In contrast, sustain pulses that are mutually in phase are applied to the pair of the Y1 and X2 electrodes defining a non-display line. Dis-

play is thus achieved over the first sub-field.

[0015] In Fig. 4, the voltage  $V_s$  is a voltage needed to induce sustain discharge and is usually set to about 170 V. Moreover, the voltage  $V_w$  is a voltage exceeding the discharge start voltage and set to about 350 V. The voltage  $-V_y$  of the scanning pulse is set to about -150 V, and the voltage  $V_a$  of the addressing pulse is set to about 60 V. The sum of the absolute values of the voltages  $V_a$  and  $V_y$  will be equal to or larger than the discharge start voltage with which discharge is initiated in the spaces defined by the addressing electrodes and each Y electrode. Moreover, the voltage  $V_x$  is set to about 50 V or a value causing discharge induced in the line defined by the addressing electrodes and each Y electrode to shift to the line defined by an X electrode. The value must enable production of sufficient wall charges.

[0016] However, according to the foregoing driving method, reset discharge is adopted. The pulse of the voltage  $V_w$  exceeding the discharge start voltage, with which discharge is initiated in discharge cells, is applied to the X electrodes. This results in intense discharge. Light emission stemming from the discharge is background light emission having no relation to the display of a picture. This leads to a deterioration in the contrast of the picture.

[0017] Moreover, in the foregoing driving method using the lines defined by all the sustain discharge electrodes as display lines, there is a possibility that reset discharge may not be induced stably in all the discharge cells. In other words, the reset pulse is applied to all the X electrodes in order to induce discharge in all display lines. A discharge start time at which discharge is initiated in each discharge cell differs from discharge cell to discharge cell. There is a possibility that discharge may not be induced in some cells.

[0018] Referring back to Fig. 2, the X2 electrode will be discussed. If discharge D2 is induced first in the line between the X2 electrode and Y1 electrode, charges stemming from the discharge start to be accumulated near the electrodes. The wall charges generate a bias voltage of the opposite polarity to the voltage  $V_w$  and an effective voltage in the discharge space decreases. More particularly, wall charges are produced on the X2 electrode due to electrons. The wall charges cause the effective voltage of the voltage  $V_w$  applied to the X2 electrode in the discharge space to drop. The drop in the effective voltage may precede the initiation of discharge in the line between the X2 electrode and Y2 electrode. In this case, although discharge is not induced in the line between the X2 electrode and Y2 electrode, the reset period may come to an end. If reset discharge is not induced in some discharge cells, the states of the cells are not uniformed. Consequently, addressing discharge cannot be induced stably in the discharge cells. This leads to erroneous display.

[0019] Even if reset discharge is induced in all the cells, subsequent self-erase discharge may not be in-

duced stably. The self-erase discharge is induced due to the potential difference generated by the wall charges stemming from reset discharge. The self-erase discharge may often be smaller in scale than the reset discharge. Depending on a difference in characteristics from discharge cell to discharge cell, the self-erase discharge may not be induced but wall charges stemming from the reset discharge may remain intact. Otherwise, when the reset discharge is completed, sufficient wall charges may not be produced and the self-erase discharge may not be induced. Consequently, subsequent addressing discharge is not induced normally in discharge cells that have not undergone erase discharge. This causes erroneous display.

**[0020]** As a method for solving the above problems, it is conceivable to raise the voltage of the reset pulse to induce discharge reliably in all cells. However, a further rise in discharge voltage will intensify the aforesaid background light emission and deteriorate the contrast of the picture.

**[0021]** If the reset period shifts to the addressing period with wall charges remaining intact in discharge cells because of the aforesaid cause, another problem arises. During the addressing period, as mentioned above, the voltage  $V_x$  is applied to X electrodes defining display lines. The other X electrodes defining non-display lines are held at 0 V, thus preventing the occurrence of addressing discharge. However, if unnecessary wall charges remain intact, discharge may be induced in the non-display lines.

**[0022]** For example, referring to Fig. 2, the scanning pulse of the voltage  $-V_y$  is applied to the Y1 electrode. The addressing pulse of the voltage  $V_a$  is applied to the addressing electrodes, whereby addressing discharge is induced. At this time, since the voltage  $V_x$  is applied to the X1 electrode, the addressing discharge is succeeded by discharge to be induced in the line between the Y1 electrode and X1 electrode. Namely, discharge D1 is induced. At this time, the X2 electrode adjoining the Y1 electrode is held at 0 V. Induction of discharge D2 can be avoided in principle. However, the discharge D2 may be induced due to deflection of residual charges deriving from uncertainty of reset discharge. Consequently, wall charges of negative polarity are accumulated on the X2 electrode. Subsequent addressing discharge D3 is affected by the wall charges. Incidentally, there is a possibility that erroneous discharge caused by electrodes not participating in the display may also be caused by a difference in discharge start voltage from discharge cell to discharge cell.

**[0023]** Moreover, sustain discharge induced during each sub-field may spread depending on the sustain discharge voltage  $V_s$  or cell structure. Referring to Fig. 4 when sustain discharge is induced in the lines between the X1 and Y1 electrodes and between the X2 and Y2 electrodes, wall charges are accumulated over the electrodes Y1 and X2 to some extent. These wall charges are erased during the reset period within each

sub-field. Wall charges formed on the addressing electrodes may not be erased but remain intact. The wall charges do not affect subsequent discharge to be induced within a field within which the lines between the X1 and Y1 electrodes and the X2 and Y2 electrodes are involved in display. The wall charges destabilize addressing discharge to be induced within the next field within which the line between the Y1 and X2 electrodes is involved in the display.

**[0024]** It is desirable to provide a method for driving a plasma display panel in which reset discharge and erase discharge can be induced reliably without deterioration in the contrast of the picture, and addressing discharge can be induced stably.

**[0025]** An embodiment of a first aspect of the present invention can provide a method for driving a plasma display panel. In the plasma display panel, pluralities of first electrodes and second electrodes are arranged parallel to each other, and a plurality of third electrodes are arranged to cross the first and second electrodes. Moreover, discharge cells defined by areas in which the electrodes cross mutually are arranged in the form of a matrix. According to the driving method, during a reset period, the distribution of wall charges in the plurality of discharge cells is made uniform. During an addressing period, wall charges are produced in discharge cells according to display data. During a sustain discharge period, sustain discharge is induced in the discharge cells in which the wall charges are produced during the addressing period. The driving method comprises a step of applying a first pulse in which an applied voltage varies with time so as to induce first discharge in the lines defined by the first and second electrodes, and a step of applying a second pulse in which an applied voltage varies with time so as to induce second discharge as erase discharge in the lines defined by the first and second electrodes. Herein, these steps are carried out during the reset period.

**[0026]** According to the above driving method, a quite feeble discharge can be induced as reset discharge. An amount of light emission is limited. Despite the reset discharge, the contrast of the picture does not deteriorate remarkably. Subsequent erase discharge is not self-erase discharge but is induced by applying a pulse in which an applied voltage varies with time. The erase discharge can be induced irrespective of a difference in characteristics from discharge cell to discharge cell or the magnitude of residual wall charges. Moreover, since the discharge is feeble, the amount of glow is limited and the contrast of the picture does not deteriorate remarkably.

**[0027]** The above-mentioned effects can be exerted even when an embodiment of the present invention is adapted to any conventional PDP in which, for example, each pair of sustain discharge electrodes provides one display line. Namely, embodiments of the present invention are not limited to a PDP in which, as described mainly in the present specification, the lines defined by all

electrodes are involved in the display.

[0028] In summary, the method for driving a plasma display panel according to an embodiment of one aspect described above of the present invention is such that the first pulse of positive polarity is applied to the second electrodes, and a pulse of negative polarity is applied to the first electrodes. Thereafter, the second pulse of negative polarity is applied to the second electrodes, and a pulse of positive polarity is applied to the first electrodes.

[0029] According to the above driving method, the second pulse is applied to be superimposed on wall charges stemming from first discharge. Erase discharge can be induced reliably by utilizing the voltages of the wall charges. Moreover, the pulse of negative polarity is applied to the first electrodes for inducing the first discharge, or the second pulse of negative polarity is applied to the second electrodes for inducing second discharge. Wall charges remaining on the addressing electrodes at the completion of sustain discharge within a previous sub-field can be erased successfully.

[0030] Preferably, the method for driving a plasma display panel is such that the pulse to be applied for inducing first discharge is applied when a period longer than at least 1  $\mu$ s has elapsed since the end of the sustain discharge period.

[0031] According to the above driving method, residual wall charges can be diminished prior to reset discharge.

[0032] Further, preferably, the method for driving a plasma display panel is such that, for inducing first discharge, the pulse of negative polarity is applied to the first electrodes before the first pulse of positive polarity is applied to the second electrodes.

[0033] According to the above driving method, wall charges remaining on the addressing electrodes can be erased, and it can be prevented that first discharge becomes intense.

[0034] Further, preferably, the method for driving a plasma display panel is such that each of the first and second pulses in which an applied voltage varies with time is a slope pulse whose voltage variation per unit time changes in magnitude.

[0035] According to the above driving method, there is a possibility that when a discharge start time differs with the state of a discharge cell, the intensity of discharge may vary. However, the method can be implemented with relatively simple circuitry.

[0036] Further, preferably, the method for driving a plasma display panel is such that each of the first and second pulses in which an applied voltage varies with time is a triangular wave whose voltage variation per unit time is constant.

[0037] According to the above driving method, although the circuitry is somewhat complex, feeble discharge can be induced reliably in all the discharge cells.

[0038] Further, preferably, the method for driving a plasma display panel is such that when the second pulse is applied, the potential at electrodes having

reached a first potential with application of the first pulse is not lowered to a second potential that is the potential at the electrodes attained prior to the application of the first pulse.

5 [0039] According to the above driving method, it can be prevented that the second discharge becomes intense.

[0040] Further, preferably, the method for driving a plasma display panel is such that the potential at electrodes having reached the first potential with the application of the first pulse is lowered to a third potential higher than the second potential, and then the second pulse is applied.

10 [0041] According to the above driving method, the second discharge does not require a long time. Besides, it can be prevented that the second discharge becomes intense.

[0042] Further, preferably, the method for driving a plasma display panel is such that the potential at electrodes to be reached with application of the second pulse is higher than the selected potential at the second electrodes during the addressing period and lower than the unselected potential at the second electrodes during the addressing period.

20 [0043] According to the above driving method, wall charges of proper magnitude can remain intact prior to addressing discharge.

[0044] According to embodiments of another aspect of the present invention, there is provided a method for driving a plasma display panel. In the plasma display panel, pluralities of first electrodes and second electrodes are arranged parallel to each other, and a plurality of third electrodes are arranged to cross the first and second electrodes. Discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix. According to the driving method, a first field and second field are temporally separated from each other. Within the first field, discharge is induced in the lines defined by the second electrodes and first electrodes adjoining one sides of the second electrodes for the purpose of display. Within the second field, discharge is induced in the lines defined by the second electrodes and first electrodes adjoining the other sides of the second electrodes for the purpose of display. The first and second fields each include a reset period, an addressing period, and a sustain discharge period. The reset period is a period during which the distribution of wall charges in the plurality of display cells is uniformed. The addressing period is a period during which wall charges are produced in discharge cells according to display data. The sustain discharge period is a period during which sustain discharge is induced in the discharge cells in which wall charges are produced during the addressing period. During the reset period, discharge is induced by applying a pulse whose applied voltage varies with the passage of time.

[0045] According to the above driving method, the lines defined by all the sustain discharge electrodes are

involved in the display. A feeble discharge can be induced as reset discharge. The magnitude of wall charges to be produced is limited. The produced wall charges will not affect adjoining display lines. Moreover, since the discharge is feeble, an amount of light emission is limited. Despite reset discharge, the contrast of the picture will not deteriorate remarkably.

**[0046]** Preferably, the method for driving a plasma display panel is such that after discharge is induced by applying the pulse, a second pulse in which an applied voltage varies with time is applied for inducing erase discharge.

**[0047]** According to the above driving method, erase discharge is not self-erase discharge but is induced by applying a pulse in which an applied voltage varies with time. The erase discharge can be induced reliably irrespective of a difference in characteristics from discharge cell to discharge cell or the magnitude of residual wall charges. Moreover, since the discharge is feeble, an amount of light emission is limited. Despite the erase discharge, the contrast of the picture will not deteriorate remarkably.

**[0048]** Further, preferably, the method for driving a plasma display panel is such that during the addressing period within the first field, a pulse of first polarity is applied to ones of the first electrodes, a pulse of second polarity is applied to the others of the first electrodes, and a scanning pulse of second polarity is applied successively to the second electrodes. During the addressing period within the second field, a pulse of first polarity is applied to the others of the first electrodes, a pulse of second polarity is applied to ones of the first electrodes, and the scanning pulse of second polarity is applied successively to the second electrodes.

**[0049]** According to the above driving method, the lines defined by all the sustain discharge electrodes are involved in the display. The potential difference among non-display lines occurring during the addressing period is limited, whereby the occurrence of erroneous discharge can be prevented.

**[0050]** According to an embodiment of still another aspect of the present invention, there is provided the method for driving a plasma display panel. In the plasma display panel, pluralities of first electrodes and second electrodes are arranged parallel to each other, and a plurality of third electrodes are arranged to cross the first and second electrodes. Discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix. According to the driving method, a first field and second field are temporally separated from each other. Within the first field, discharge is induced in the lines defined by the second electrodes and first electrodes adjoining one sides of the second electrodes for the purpose of display. Within the second field, discharge is induced in the lines defined by the second electrodes and first electrodes adjoining the other sides of the first electrodes for the purpose of display. The first and second fields are each composed of a field reset

period and a plurality of sub-fields. Each sub-field includes a reset period, an addressing period, and a sustain discharge period. The field reset period is a period during which discharge is induced for erasing wall charges remaining at the end of a previous field. The reset period is a period during which the distribution of wall charges in a plurality of discharge cells is uniformed. The addressing period is a period during which wall charges are produced in discharge cells according to display data. The sustain discharge period is a period during which sustain discharge is induced in the discharge cells in which wall charges are produced during the addressing period.

**[0051]** According to the above driving method, the lines defined by all the sustain discharge electrodes are involved in display. Wall charges remaining at the end of a previous field can be erased.

**[0052]** Preferably, the method for driving a plasma display panel is such that the field reset period is composed of four periods. During one of the four periods, discharge is induced in the lines defined by first even-numbered electrodes and second odd-numbered electrodes. During another period, discharge is induced in the lines defined by first odd-numbered electrodes and second even-numbered electrodes. During still another period, discharge is induced in the lines defined by the first odd-numbered electrodes and second odd-numbered electrodes. During the other period, discharge is induced in the lines between the first even-numbered electrodes and second even-numbered electrodes.

**[0053]** According to the above driving method, wall charges produced on the electrodes, especially, on the addressing electrodes can be erased reliably.

**[0054]** Further, preferably, the method for driving a plasma display is such that the discharge to be induced during the field reset period is accompanied by self-erase discharge. The self-erase discharge is induced by the potential difference generated by the wall charges. The wall charges are produced with the potential at the electrodes set to the same value after reset discharge is induced by applying a pulse to the electrodes.

**[0055]** According to the above driving method, after reset discharge is induced, wall charges can be erased stably by self-erase discharge.

**[0056]** Further, preferably, the method for driving a plasma display panel is such that the first and second fields each include a field reset charge adjustment period preceding the field reset period. The field reset charge adjustment period is a period during which wall charges are produced to be superimposed on charges released during the field reset period.

**[0057]** According to the above driving method, field reset can be achieved stably irrespective of the states of discharge cells attained at the end of an immediately preceding field.

**[0058]** Further, preferably, the method for driving a plasma display panel comprises a step of applying a first pulse in which an applied voltage varies with time, so as

to induce discharge, and a step of applying a second pulse, in which an applied voltage varies with time, so as to adjust the magnitude of wall charges produced with the first pulse. These two steps are carried out during the field reset charge adjustment period.

[0059] According to the above driving method, wall charges to be superimposed on charges released during field reset can be left at a proper magnitude. Discharge to be induced in the field reset charge adjustment period is therefore a feeble discharge.

[0060] Reference will now be made, by way of example, to the accompanying drawings, in which:

Fig. 1, discussed hereinbefore, is a schematic diagram showing the structure of a surface discharge type PDP;

Fig. 2, discussed hereinbefore, is a sectional view of the PDP shown in Fig. 1 along an A1 addressing electrode;

Fig. 3, discussed hereinbefore, shows a frame configuration employed in the PDP shown in Fig. 1;

Fig. 4, discussed hereinbefore, is a waveform diagram illustrating a driving method implemented in the PDP shown in Fig. 1;

Fig. 5 is a waveform diagram illustrating a first embodiment of the present invention;

Fig. 6 shows a frame configuration employed in the first embodiment of the present invention;

Fig. 7 is a waveform diagram illustrating field reset employed in the first embodiment of the present invention;

Fig. 8 is a waveform diagram illustrating a second embodiment of the present invention;

Fig. 9 is a waveform diagram illustrating a third embodiment of the present invention;

Fig. 10 is a waveform diagram illustrating a fourth embodiment of the present invention;

Fig. 11 is a waveform diagram illustrating a fifth embodiment of the present invention;

Fig. 12 shows a frame configuration employed in a sixth embodiment of the present invention; and

Fig. 13 is a waveform diagram illustrating the sixth embodiment of the present invention.

[0061] Fig. 5 is a waveform diagram illustrating a first embodiment of the present invention. In Fig. 5, there are shown the waveforms of voltages to be applied to addressing electrodes, an X1 electrode, a Y1 electrode, an X2 electrode, and a Y2 electrode during a sub-field within a first field. Odd lines are involved in display within the first field. The sub-field consists of a reset period, an addressing period, and a sustain discharge period. Hereinafter, the X1 and X2 electrodes shall be referred to as X electrodes, the Y1 and Y2 electrodes shall be referred to as Y electrodes, and all of them shall be referred to as sustain discharge electrodes.

[0062] During the reset period, the addressing electrodes are set to 0 V, and pulses of positive and negative

polarities are applied to the sustain discharge electrodes. Specifically, a pulse of a voltage  $-V_{wx}$  is applied to the X electrodes, and a pulse of a voltage  $V_{wy}$  is applied to the Y electrodes. The pulse to be applied to the Y electrodes is a pulse of gentle slope that reaches the voltage  $V_{wy}$  with its voltage variation per unit time changed. Consequently, first feeble discharge is induced in the lines defined by the X electrodes and Y electrodes.

[0063] When a rectangular wave  $V_w$  similar to a conventional one is applied as an applied voltage, intense discharge is induced proportional to a difference  $V_w - V_f$  from a discharge start voltage  $V_f$  to be applied to initialize discharge in discharge cells. Excess wall charges are produced to affect adjoining discharge cells. However, since a slope pulse is adopted, when the applied voltage exceeds the discharge start voltage  $V_f$  to be applied to each discharge cell, each discharge cell starts discharging. The induced discharge is merely feeble. The magnitude of produced wall charges is small. Consequently, even if reset discharge is induced earlier in a certain discharge cell, the reset discharge will not affect adjoining discharge cells. Moreover, since the discharge is feeble, background glow is weak.

[0064] Thereafter, a pulse of a voltage  $V_{ex}$  is applied to the X electrodes, and a pulse of a voltage  $-V_{ey}$  is applied to the Y electrodes. The pulse applied to the Y electrodes is a slope pulse that reaches a voltage  $-V_{ey}$  while changing in magnitude its voltage variation per unit time. This induces second discharge, whereby wall charges stemming from the immediately preceding discharge are erased.

[0065] When self-erase discharge is employed as it is conventionally, discharge may not be induced depending on the magnitude of wall charges produced or the characteristic of discharge cells. According to the present invention, discharge is forcibly induced by applying a voltage  $V_{ex} + V_{ey}$ . Erase discharge is therefore induced reliably. Furthermore, since an applied pulse is a slope pulse, discharge is feeble. The contrast of the picture will not deteriorate. Moreover, the voltage  $V_{ex} + V_{ey}$  is set to be slightly lower than the discharge start voltage  $V_f$ . Wall charges of diminutive magnitude stemming from the first discharge are superimposed on the voltage, whereby erase discharge is induced.

[0066] Sustain discharge is induced fundamentally in the lines defined by the X and Y electrodes. Meanwhile, the addressing electrodes are retained at a potential lower than a sustain discharge voltage  $V_s$ . Wall charge of positive polarity are therefore produced on the addressing electrodes. For the first discharge in this embodiment, the pulse of negative polarity is applied to the X electrodes. Discharge is induced in the spaces defined by the addressing electrodes and X electrodes, and released charges are superimposed on the wall charges remaining on the addressing electrodes. Consequently, the wall charges remaining on the addressing electrodes above the X electrodes are erased. For the

subsequent second discharge, the pulse of negative polarity is applied to the Y electrodes. Wall charges remaining on the addressing electrodes above the Y electrodes are erased.

**[0067]** Thereafter, during the addressing period, addressing discharge is induced by applying a scanning pulse successively to the Y electrodes. A voltage  $V_x$  is, conventionally, applied to X electrodes that are paired with the Y electrodes, to which the scanning pulse has been applied, to define display lines. Consequently, addressing discharge is induced. In contrast, a voltage  $-V_{ux}$  is applied to X electrodes defining non-display lines. A potential difference from the Y electrodes is thus limited in order to prevent addressing discharge from being induced in the non-display lines. The scanning pulse is applied successively to the odd-numbered Y electrodes in order to induce addressing discharge. Thereafter, the scanning pulse is applied successively to the even-numbered Y electrodes in order to induce addressing discharge. This procedure is the same as that in the conventional method.

**[0068]** After the addressing period elapses, the sustain discharge period starts. A sustain pulse is applied alternately to the X electrodes and Y electrodes. Sustain discharge is induced repeatedly in cells having undergone addressing discharge during the addressing period. At this time, the phase of the sustain discharge pulse is determined as it conventionally is, so that sustain discharge will not be induced in non-display lines.

**[0069]** Referring to Fig. 5, the sum of the absolute values of the voltages  $-V_{wx}$  and  $V_{wy}$  to be applied during the reset period is set to a value exceeding the value of a discharge start voltage. The discharge start voltage is a voltage with which discharge is initiated in the lines defined by X and Y electrodes. For example, the voltage  $-V_{wx}$  is set to  $-130$  V, and the voltage  $V_{wy}$  is set to  $220$  V. For the subsequent erase discharge, for example, the voltage  $V_{ex}$  is set to  $60$  V, and the voltage  $-V_{ey}$  is set to  $-160$  V. Moreover, for the addressing period, the voltage  $V_a$  is set to, for example,  $60$  V, the voltage  $-V_y$  of the scanning pulse is set to, for example,  $-150$  V. The voltage  $V_x$  to be applied to the X electrodes is set to, for example,  $50$  V, and the voltage  $-V_{ux}$  is set to, for example,  $-80$  V. Moreover, the voltage  $V_s$  of the sustain pulse is set to, for example,  $170$  V. Moreover, the voltages  $V_{ex}$  and  $V_x$  or  $-V_{ey}$  and  $-V_y$  may be set to the same voltage. In this case, a circuit can be used in common, and the scale of circuitry can be suppressed.

**[0070]** Fig. 6 shows a frame configuration employed in the first embodiment of the present invention. A difference from the one shown in Fig. 3 lies in a point that a field reset period is defined at the start of each field. The field reset period is a period during which wall charges remaining on the addressing electrodes are erased at the time of a field-to-field transition.

**[0071]** Fig. 7 is a waveform diagram concerning field reset employed in the first embodiment of the present invention. At a time instant  $t_1$ , a voltage  $-V_y$  is applied

to the Y electrodes, and a voltage  $V_s$  is applied to the X2 electrodes. Consequently, discharge is induced and wall charges are produced. Thereafter, the pulses are removed and the potentials at the electrodes are held at the same value. Self-erase discharge is induced due to potential differences among the produced wall charges, whereby the wall charges are erased. Similarly, reset discharge is induced sequentially in all the lines defined by the electrodes at four times starting with a time instant  $t_2$  and ending with a time instant  $t_4$ . Wall charges are reliably erased. In this embodiment, discharge is induced in the lines defined by the odd-numbered Y electrodes and even-numbered X electrodes at the time instant  $t_1$ . Discharge is induced in the lines defined by the odd-numbered X electrodes and even-numbered Y electrodes at the time instant  $t_2$ . Discharge is induced in the lines defined by the odd-numbered X electrodes and odd-numbered Y electrodes at the time instant  $t_3$ . Discharge is induced in the lines defined by the even-numbered X electrodes and even-numbered Y electrodes at the time instant  $t_4$ . It can be determined arbitrarily as to in which lines discharge is induced at the time instants  $t_1$  to  $t_4$ .

**[0072]** In the aforesaid first embodiment, a pulse to be applied to the Y electrodes for first and second discharge is a slope pulse whose voltage variation per unit time changes in magnitude. The pulsating wave can be produced readily by constructing an RC circuit that consists of resistors  $R$  connected to a switching device for outputting a pulse and electrostatic capacitors  $C$  created among electrodes. A curve plotted by tracing the slope pulse is determined by the time constant defined by the RC circuit.

**[0073]** However, when the slope pulse is employed, the voltage variation of the pulse per unit time changes in magnitude with the rise or fall of the pulse. This causes a problem in that the intensity of discharge varies depending on at what time instant discharge is initiated. When the pulse is saturated to approximate a set voltage, if discharge is initiated, very feeble discharge can be realized. However, discharge may be initiated in a relatively early stage because of a difference in characteristics from discharge cell to discharge cell, that is, discharge may be initiated at the relatively sharp leading or trailing edge of the pulse. In this case, intense discharge may be induced, and wall charges of great magnitude may be produced.

**[0074]** Fig. 8 is a waveform diagram illustrating the second embodiment of the present invention. This embodiment is such that a pulse to be applied to the Y electrodes for the first and second discharge is a triangular wave whose voltage variation per unit time is constant in magnitude. According to this embodiment, the circuitry for producing the triangular wave is somewhat more complex than that in the first embodiment. However, since the slope of the pulse is constant, feeble discharge can be induced reliably.

**[0075]** Fig. 9 is a waveform diagram illustrating the



third embodiment of the present invention. Fig. 9 is concerned with a time instant during a sustain discharge period within a sub-field, at which the last pulse is applied, and a reset period within the next sub-field. In this embodiment, a slope pulse whose voltage variation per unit time changes in magnitude is adopted as a pulse to be applied to the Y electrodes for the first and second discharge. From this viewpoint, the third embodiment is identical to the first embodiment. However, in this embodiment, it is designed that sufficient time has elapsed from the leading edge of the sustain discharge pulse to be applied during the sustain discharge period within the sub-field, to the application of a pulse during the reset period within the next sub-field.

**[0076]** When sustain discharge is induced with application of the sustain pulse, wall charges of predetermined magnitude are accumulated with the completion of discharge. When a certain time has elapsed since the completion of discharge, produced wall charges start neutralizing spatial charges existent in discharge spaces. After sufficient time has passed since the application of the last sustain pulse, reset discharge is induced. In this way, wall charges remaining at the end of the sustain discharge period can be erased to some extent. Consequently, the subsequent reset discharge can be induced with fewer residual wall charges. The reset discharge can therefore be induced stably. The time from the trailing edge of the sustain discharge pulse to the initiation of the next reset discharge,  $t_1$ , should be longer than at least 1  $\mu\text{s}$ , or preferably, should be 10  $\mu\text{s}$ .

**[0077]** Moreover, in this embodiment, for the first discharge to be induced during the reset period, a pulse of negative polarity is applied to the X electrodes and a pulse of positive polarity is applied to the Y electrodes. At this time, the timing of applying the pulse of negative polarity is different from that of applying the pulse of positive polarity.

**[0078]** As mentioned in relation to the first embodiment, a pulse of negative polarity and a pulse of positive polarity are applied to the X electrodes and Y electrodes respectively at the same time. In this case, although a slope pulse is employed, intense discharge may be induced. In this embodiment, the timing of applying a pulse of negative polarity to the X electrodes is differentiated from the one of applying a pulse of negative polarity to the Y electrodes.

**[0079]** As mentioned above, a pulse of negative polarity to be applied to the X electrodes for first discharge exerts the effect of erasing wall charges remaining on the addressing electrodes. When the erase discharge is induced earlier, wall charges of positive polarity are produced on the X electrodes, to which the pulse of negative polarity has been applied, along with the erasure of wall charges on the addressing electrodes. If a second pulse of positive polarity is applied to the Y electrodes in this state, an effective voltage in the lines defined by the X and Y electrodes drops to prevent intense discharge. For merely preventing intense discharge, the

voltage of negative polarity to be applied to the X electrodes is lowered according to a method. In this case, it becomes difficult to induce erase discharge in the spaces below the addressing electrodes. This is not preferable.

**[0080]** A delay time  $t_2$  from the application of a pulse to the X electrodes to application of a pulse to the Y electrodes should be at least about 5  $\mu\text{s}$ .

**[0081]** Fig. 10 is a waveform diagram illustrating the fourth embodiment of the present invention, wherein only the waveform of a voltage to be applied to the Y electrodes during the reset period is illustrated. A pulse to be applied to the Y electrodes is a slope pulse whose voltage variation per unit time changes in magnitude.

**[0082]** In the aforesaid first to third embodiments, the potential at the Y electrodes which has reached  $V_{wy}$  is lowered to 0 V at the time of second discharge succeeding first discharge. Thereafter, a pulse for inducing the second discharge is applied. However, when the potential at the Y electrodes is lowered to 0 V, if high voltages are concurrently applied to the electrodes, intense discharge may be induced. When the application of a pulse of positive polarity to the X electrodes and the application of a pulse of negative polarity to the Y electrodes are concurrently carried out for the second discharge, it means that the high voltages are concurrently applied to the electrodes.

**[0083]** According to this embodiment, in the case of a portion "a" of Fig. 10, the potential at the Y electrodes is not lowered to 0 V but the pulse for inducing the second discharge is applied immediately. This can prevent concurrent application of high voltages to the electrodes. Consequently, intense discharge can be avoided.

**[0084]** However, the case of the portion "a" of Fig. 10 poses a problem in that the time required for the second discharge gets longer. This is because the potential at the Y electrodes is dropped from  $W_{wy}$  to  $-V_{ey}$  using a slope pulse. For shortening the time required for the second discharge, a voltage variation per unit time must be increased in magnitude. Consequently, the scale of the second discharge expands and the contrast of the picture deteriorates.

**[0085]** The case of a portion "b" of Fig. 10 stands in the middle of the first to third embodiments and the case of the portion "a" of Fig. 10. Namely, the potential at the Y electrodes that has reached  $V_{wy}$  is lowered to a potential higher than 0 V (for example, about 20 V). Thereafter, a pulse of negative polarity that is a slope pulse is applied.

**[0086]** For example, the potential at the Y electrodes that has reached  $V_{wy}$  is lowered to  $V_s$  by connecting the Y electrodes to a power supply  $V_s$  for sustain discharge. Furthermore, a power collection circuit connected to the Y electrodes is used to lower the potential at the Y electrodes to a predetermined value. This technique is readily adopted. The power collection circuit is realized with a series resonant circuit composed of an

inductor connected to the Y electrodes (or X electrodes) and a panel capacitor. The power collection circuit collects and reuses the sustain voltage  $V_s$  applied to the electrodes. During the sustain discharge period, the sustain voltage  $V_s$  is applied alternately to the X and Y electrodes. This action is equivalent to charging and discharging of the panel capacitor realized with the lines defined by the X and Y electrodes. The power collection circuit effectively utilizes the charging current and discharging current. The power collection circuit is indispensable to low power consumption to be attained in a PDP. By utilizing the power collection circuit, the potential at the Y electrodes can be lowered without addition of a new circuit.

**[0087]** After the potential at the Y electrodes is lowered to a predetermined value, the Y electrodes are connected to a conventional circuit for generating a slope erase pulse. Consequently, in this case, neither intense discharge will be induced nor the magnitude of a voltage variation per unit time will be increased. Nevertheless, the time required for the second discharge can be shortened.

**[0088]** Fig. 11 is a waveform diagram illustrating the fifth embodiment of the present invention. In this embodiment, when the second discharge is completed, the potential at the Y electrodes reaches a potential higher than  $-V_y$  that is the voltage of the scanning pulse.

**[0089]** A slope pulse which is to be applied to the Y electrodes for the second discharge has a negative polarity. Positive wall charges are therefore produced on the Y electrodes. In the aforesaid first to fourth embodiments, the potential at the Y electrodes is lowered to  $-V_y$  that is the voltage of the scanning pulse. Produced wall charges are of relatively great magnitude. During the subsequent addressing period, the scanning pulse of negative polarity is applied to the Y electrodes. At this time, if positive wall charges remain intact, the effective voltage of the scanning pulse is lowered. This leads to a possibility of hindering stable induction of addressing discharge. In contrast, the potential at the Y electrodes may be too high at the completion of the second discharge (for example, the unselected potential  $-V_{sc}$  at Y electrodes during the addressing period). In this case, negative wall charges are produced on the Y electrodes. Consequently, when the scanning pulse of negative polarity is applied to the Y electrodes, the negative wall charges are superimposed on the scanning pulse. Eventually, there arises a possibility that discharge may be induced in cells in which the addressing pulse has not been applied.

**[0090]** In this embodiment, the potential at the Y electrodes attained at the completion of the second discharge is an intermediate one between the selected potential  $-V_y$  at Y electrodes during the addressing period and the unselected potential  $-V_{sc}$  at Y electrodes. Addressing discharge can therefore be induced stably. Otherwise, for ensuring the same margin for driving as a conventionally ensured one, the applied voltage of the

addressing pulse may be lowered. The potential at the Y electrodes to be attained should be set so that a rise  $\Delta V$  from the selected potential  $-V_y$  at Y electrodes during the addressing period will fall within a range of  $0 < \Delta V < 20$  V, or preferably, will be approximately 10 V.

**[0091]** Fig. 12 shows a frame configuration employed in the sixth embodiment of the present invention. Fig. 13 is a waveform diagram illustrating the sixth embodiment. The sixth embodiment is identical to the first embodiment in a point that the field reset period described in conjunction with Fig. 6 is adopted. The sixth embodiment is characterized in that a field reset charge adjustment period (i.e., field reset charge adjusting period) is adopted.

**[0092]** After the first field or second field elapses, the states of charges in the cells are mutually different. This is because the discharged states of the cells attained within each field are mutually different. If wall charges whose polarity is opposite to that of an applied pulse used to carry out field reset remain intact at the start of the field reset period, the effective voltage of the applied pulse is lowered. This makes it difficult to carry out field reset stably. For example, in the example of Fig. 7, if positive wall charges remain intact on the Y1 electrode (or negative wall charges remain intact on the X2 electrode), effective voltages to be applied to the Y1 and X2 electrodes are lowered. This disables stable discharge. In this embodiment, the field reset period is preceded by the field reset charge adjustment period. Wall charges whose polarity is the same as that of a pulse to be applied during the field reset period are produced actively.

**[0093]** Fig. 13 is a practical waveform diagram. During the field reset charge adjustment period, first, a pulse of negative polarity is applied to the X1 electrode, and a pulse of positive polarity is applied to the Y1 electrode. The sum of the voltage  $V_{wx}$  applied to the X1 electrode and the voltage  $V_{wy}$  applied to the Y1 electrode exceeds a discharge start voltage with which discharge is initiated in each cell. Consequently, discharge is initiated in all the cells. At this time, the pulse to be applied to the Y1 electrode is a slope pulse whose voltage variation per unit time changes in magnitude. The discharge is therefore, similarly to the first discharge induced during the reset period, a feeble discharge. A deterioration in the contrast of the picture can therefore be suppressed. The whole-surface discharge causes negative wall charges to be accumulated on the Y1 electrode. However, the accumulated wall charges are of great magnitude. If the field reset charge adjustment period is shifted to the field reset period in this state, discharge becomes too large in scale due to superimposition of wall charges. An erase pulse of negative polarity is therefore applied to the Y1 electrode, whereby the magnitude of accumulated wall charges is adjusted. The pulse of negative polarity is a slope pulse whose voltage variation per unit time changes in magnitude.

**[0094]** Consequently, negative wall charges of proper

magnitude are accumulated at the end of the field reset charge adjustment period. When the field reset charge adjustment period is shifted to the field reset period in this state, the produced wall charges are superimposed on an applied pulse. Field reset can be carried out reliably.

[0095] As explained above, using an embodiment of the present invention, a deterioration in the contrast of the picture can be suppressed. Besides, reset discharge and subsequent erase discharge can be induced reliably in all display lines. Consequently, the states of all the cells can be reliably uniformed during the reset period. Eventually, addressing discharge can be induced stably and erroneous display can be prevented.

#### Claims

1. A method for driving a plasma display panel in which pluralities of first electrodes and second electrodes are arranged parallel to each other adjacently, a plurality of third electrodes are arranged to cross the pairs of first and second electrodes, and discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix; wherein

a reset period is defined as a period during which the distribution of wall charges in the plurality of discharge cells is made uniform; an addressing period is defined as a period during which wall charges are produced in the discharge cells according to display data; a sustain discharge period is defined as a period during which sustain discharge is induced in the discharge cells in which wall charges are produced during the addressing period; and said method for driving a plasma display panel comprises the steps of:

applying a first pulse in which an applied voltage varies with time so as to induce first discharge in the lines defined by said first and second electrodes; and

applying a second pulse in which an applied voltage varies with time so as to induce second discharge as erase discharge in the lines defined by said first and second electrodes, these steps being carried out during said reset period.

2. A method for driving a plasma display panel according to claim 1, wherein said first pulse of positive polarity is applied to said second electrodes and a pulse of negative polarity is applied to said first electrodes, and then said second pulse of negative polarity is applied to said second electrodes and a pulse of positive polarity is applied to said first electrodes.

3. A method for driving a plasma display panel according to claim 1 or 2, wherein, when a period exceeding at least 1  $\mu$ s has elapsed since the end of said sustain discharge period, said pulses for inducing said first discharge is applied.

4. A method for driving a plasma display panel according to claim 2 or 3 wherein, for said first discharge, before said first pulse of positive polarity is applied to said second electrodes, said pulse of negative polarity is applied to said first electrodes.

5. A method for driving a plasma display panel according to any preceding claim, wherein each of said first and second pulses in which an applied voltage varies with time is a slope pulse whose voltage variation per unit time changes in magnitude.

6. A method for driving a plasma display panel according to any one of claims 1 to 4, wherein each of said first and second pulses in which an applied voltage varies with time is a triangular wave whose voltage variation per unit time is constant in magnitude.

7. A method for driving a plasma display panel according to any preceding claim, wherein when said second pulse is applied, the potential at the electrodes having reached a first potential with application of said first pulse is not lowered to a second potential that is the potential at the electrodes attained before the application of said first pulse.

8. A method for driving a plasma display panel according to claim 7, wherein after the potential at the electrodes that having reached said first potential with application of said first pulse is lowered to a third potential that is higher than said second potential, said second pulse is applied.

9. A method for driving a plasma display panel according to any preceding claim, wherein the potential at the electrodes to be reached with application of said second pulse is higher than the selected potential at said second electrodes during said addressing period and lower than the unselected potential at said second electrodes during said addressing period.

10. A method for driving a plasma display panel in which pluralities of first electrodes and second electrodes are arranged parallel to each other, a plurality of third electrodes are arranged to cross the first and second electrodes, and discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix;

wherein a first field during which discharge is induced in the lines defined by said second

electrodes and said first electrodes adjoining one sides of said second electrodes for the purpose of display, and a second field during which discharge is induced in the lines defined by said second electrodes and said first electrodes adjoining the other sides thereof for the purpose of display are temporally separated from each other;

said first and second fields each include a reset period during which the distribution of wall charges in said plurality of discharge cells is uniformed, an addressing period during which wall charges are produced in the discharge cells according to display data, and a sustain discharge period during which sustain discharge is induced in the discharge cells in which wall charges are produced during said addressing period; and

during said reset period, a pulse in which an applied voltage varies with time is applied for inducing discharge.

11. A method for driving a plasma display panel according to claim 10, wherein after discharge is induced by applying said pulse, a second pulse in which an applied voltage varies with time is applied for inducing erase discharge.

12. A method for driving a plasma display panel according to claim 10, wherein during said addressing period within said first field, a pulse of first polarity is applied to ones of said first electrodes, a pulse of second polarity is applied to the others of said first electrodes, and then a scanning pulse of second polarity is applied successively to said second electrodes;

during said addressing period within said second field, a pulse of first polarity is applied to the others of said first electrodes, a pulse of second polarity is applied to ones of said first electrodes, and then a scanning pulse of second polarity is applied successively to said second electrodes.

13. A method for driving a plasma display panel in which pluralities of first electrodes and second electrodes are arranged parallel to each other, a plurality of third electrodes are arranged to cross the first and second electrodes, and discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix;

wherein a first field within which discharge is induced in the lines defined by said second electrodes and said first electrodes adjoining one sides of said second electrodes for the purpose of display, and a second field within which

discharge is induced in the lines defined by said second electrodes and said first electrodes adjoining the other sides thereof for the purpose of display are temporally separated from each other; and

said first and second fields each include a field reset period during which discharge is induced for erasing wall charges remaining at the end of a previous field and a plurality of sub-fields each consisting of a reset period during which the distribution of wall charges in said plurality of discharge cells is uniformed, an addressing period during which wall charges are produced in discharge cells according to display data, and a sustain discharge period during which sustain discharge is induced in the discharge cells in which wall charges are produced during said addressing period.

14. A method for driving a plasma display panel according to claim 13, wherein said field reset period consists of a period during which discharge is induced in the lines defined by first even-numbered electrodes and second odd-numbered electrodes, a period during which discharge is induced in the lines defined by first odd-numbered electrodes and second even-numbered electrodes, a period during which discharge is induced in the lines defined by the first odd-numbered electrodes and second odd-numbered electrodes, and a period during which discharge is induced in the lines defined by the first even-numbered electrodes and second even-numbered electrodes.

15. A method for driving a plasma display panel according to claim 14, wherein each discharge induced during said field reset period is accompanied by self-erase discharge that after reset discharge is induced by applying a pulse to electrodes, is induced by the potential difference generated by wall charges stemming from reset discharge with the potentials at the electrodes set at the same value.

16. A method for driving a plasma display panel according to any one of claims 13 to 15, wherein said first and second fields each include a field reset charge adjustment period which precedes said field reset period and during which wall charges are produced to be superimposed on charges released during said field reset period.

17. A method for driving a plasma display panel according to claim 16, further comprising a step of inducing discharge by applying a first pulse in which an applied voltage varies with time, and a step of applying a second pulse in which an applied voltage varies with time so as to adjust the magnitude of wall charges produced with said first pulse, wherein

these steps are carried out during said field reset charge adjustment period.

18. Apparatus for driving a plasma display panel in which pluralities of first electrodes and second electrodes are arranged parallel to each other adjacently, a plurality of third electrodes are arranged to cross the pairs of first and second electrodes, and discharge cells defined with areas in which the electrodes cross mutually are arranged in the form of a matrix; wherein

a reset period is defined as a period during which the distribution of wall charges in the plurality of discharge cells is made uniform;  
an addressing period is defined as a period during which wall charges are produced in the discharge cells according to display data;  
a sustain discharge period is defined as a period during which sustain discharge is induced in the discharge cells in which wall charges are produced during the addressing period; and  
said apparatus comprises :  
means for applying a first pulse during a reset period in which first pulse an applied voltage varies with time so as to induce first discharge in the lines defined by said first and second electrodes; and  
means for applying a second pulse during a reset period, in which second pulse an applied voltage varies with time so as to induce second discharge as erase discharge in the lines defined by said first and second electrodes.

35

40

45

50

55

Fig.1




Fig.2






Fig.3










Fig.5

Fig.6





Fig.7






Fig.9





Fig.10







Fig.12








Fig.13

European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 00 30 4900

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 97 20301 A (PLASMACO INC.) 5 June 1997 (1997-06-05)	1,2,4,6,18	G09G3/28
Y	* abstract *	5,10,11	
A	* page 7, line 3 - line 33 * * page 8, line 16 - line 34 * * page 16, line 28 - page 17, line 21 * * page 19, line 34 - page 20, line 10; figure 11 *	3,7-9,12	
X	EP 0 680 067 A (MATSUSHITA ELECTRONICS CORP.) 2 November 1995 (1995-11-02)	1,2,4,6,18	
Y	* column 39, line 7 - column 42, line 23 *	5,10,11	
A	* column 47, line 43 - line 49 * * column 52, line 17 - column 56, line 58; figures 20-23,28-33 *	3,7-9,12	
Y	US 5 663 741 A (KANAZAWA) 2 September 1997 (1997-09-02)	5,10	
A	* column 7, line 21 - column 8, line 21 *  * column 15, line 30 - column 18, line 11; figures 10-21 *	1-4,6-9,11,12	
Y,D	EP 0 762 373 A (FUJITSU LTD.) 12 March 1997 (1997-03-12)	10,11	
A	* abstract *  * column 14, line 20 - column 16, line 16 * * column 18, line 32 - column 19, line 14; figures 1-8 *	1-9,12-18	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>22 September 1999</b>	Examiner <b>O'Reilly, D</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.92 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 4808

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

22-09-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9720301 A	05-06-1997	US 5745086 A	28-04-1998
		AU 705338 B	20-05-1999
		AU 1076697 A	19-06-1997
		CA 2233686 A	05-06-1997
		CN 1203684 A	30-12-1998
		EP 0864141 A	16-09-1998
EP 680067 A	02-11-1995	JP 7296734 A	10-11-1995
		JP 7312178 A	28-11-1995
		JP 7319424 A	08-12-1995
		JP 7320644 A	08-12-1995
		JP 8030228 A	02-02-1996
		JP 8030227 A	02-02-1996
		JP 8212930 A	20-08-1996
		JP 8063110 A	08-03-1996
		CA 2147902 A	29-10-1995
		CN 1119336 A	27-03-1996
		FI 952020 A	29-10-1995
		US 5656893 A	12-08-1997
US 5663741 A	02-09-1997	JP 6314078 A	08-11-1994
		FR 2704674 A	04-11-1994
EP 762373 A	12-03-1997	CN 1157449 A	20-08-1997
		JP 2801909 B	21-09-1998
		JP 10307560 A	17-11-1998
		JP 2801893 B	21-09-1998
		JP 9160525 A	20-06-1997

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office. No. 12/82